



**professional grade reinforced**

# Polyurethane Air Hose

*with 1/4" M-NPT brass male fittings, solid repairable ends and a strain relief; coupler and plug included on new items.*

## Reinforced Polyurethane Air Hose Features:

- 200 PSI working pressure @ 70°F/ 21°C
- Stays flexible in sub-zero temperatures -40°F to +165°F
- 40% lighter than standard PVC and rubber air hose
- Abrasion and kink resistant



**DURA**  
by INTERCHANGE **FLX+**

*Lightweight yet holds up to extremely tough conditions.*



### Green Hose with 1/4" M-NPT Brass Male Fittings, Coupler and Plug

Item No.	Sort Name	Size
94522	PU-14X50WF-GRN	1/4" x 50'
94527	PU-14x100WF-GRN	1/4" x 100'
94582	PU-38X50WF-GRN	3/8" x 50'
94592	PU-38X100WF-GRN	3/8" x 100'



### Titanium Hose with 1/4" M-NPT Brass Male Fittings, Coupler and Plug

Item No.	Sort Name	Size
94523	PU-14X50WF-TITAN	1/4" x 50'
94526	PU-14X100WF-TITA	1/4" x 100'
94562	PU-38X50WF-TITAN	3/8" x 50'
94567	PU-38X100WF-TITA	3/8" x 100'



### Orange Hose with 1/4" M-NPT Brass Male Fittings, Coupler and Plug

Item No.	Sort Name	Size
94524	PU-14X50WF-ORANG	1/4" x 50'
94528	PU-14X100WF-ORAN	1/4" x 100'
94563	PU-38X50WF-ORANG	3/8" x 50'
94568	PU-38X100WF-ORAN	3/8" x 100'

**INTERCHANGE  
Brands, LLC**

[www.interchangebrands.com](http://www.interchangebrands.com)

1-800-458-6635